SDS

SAFETY DATA SHEET

Prepared For: SHENZHEN GMCELL TECHNOLOGY CO., LTD

Hualian Panorama International Building, 27

District, Bao'an, Shenzhen, China

Prepared By: Shenzhen LCS Compliance Testing Laboratory Ltd.

101, 201 Building A and 301 Building C, Juji

Industrial Park, Yabianxueziwei, Shajing Street,

Baoan District, Shenzhen, Guangdong, China

Issue Date : 2021.01.04

Report

: CS201216148ASD

Number

Written by: <u>Seven Jau</u> Approved by

Version: V1.4
REPORT

NO.:CS201216148ASD

* The SDS is prepared based on the information provided by client. The contents and formats of this SDS are revised as per client's request.

	Section 1- Identification				
(a) Product identifier					
Product name	Super Heavy Duty Battery				
(b) Other means of ident	ification				
Product description	Model: R6P, R03P, 6F22, R1P, R14P, R20P, 3R22, Nominal Voltage: 1.5V Weight: 6.6g	4R25			
(c) Recommended use of	f the chemical and restrictions on use				
Recommended use	Alkaline Battery				
Uses advised against	No information available.				
(d) Details of the supplie	er of the safety data sheet				
Supplier Name	SHENZHEN GMCELL TECHNOLOGY CO., LTD				
Supplier Address	Hualian Panorama International Building, 27 District, Bao'an, Shenzhen, China				
Manufacture Company	SHENZHEN GMCELL TECHNOLOGY CO., LTD	SHENZHEN GMCELL TECHNOLOGY CO., LTD			
Manufacture Address	Hualian Panorama International Building, 27 District, Bao'an, Shenzhen, China				
Supplier Phone Number	Number +86-755-29497371				
(e) Emergency telephon	e number				
+86-755-29497371					
	Section 2- Hazards Identificati	on			
(a) Classification This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.					
Harmful if swallowed Category 4					
Causes severe skin burns and eye damage Category 1A					
(b) GHS Label elements,	including precautionary statements				
Emergency Overview					
Signal word Danger					

Version: V1.4
REPORT

NO.:CS201216148ASD

Hazard Statements

Harmful if swallowed Causes severe skin burns and eye damage





Appearance: No information available	Physical State: Solid	Odor: No information available
P102	Keep out of reach of children.	
P260	Do not breathe dust/fume/gas/mist/	vapours/spray
P261	Avoid breathing dust/fume/gas/mist	/vapours/spray
P264	Wash thoroughly after handling	
P270	Do not eat, drink or smoke when us	sing this product.
P271	Use only outdoors or in a well-venti	lated area
P280	Wear protective gloves/protective c	lothing/eye protection/face protection
	IF SWALLOWED: Call a POISON Cunwell.	CENTER/doctor/\u2026if you feel
P301+P312	Rinse mouth	
P330.	IF SWALLOWED: Rinse mouth. Do	•
P301+P330+P331 P303+P361+P353	Call a POISON CENTER/doctor/\u2	2026if you feel unwell.
P312	Rinse mouth	
P330	IF ON SKIN (or hair): Take off imme	ediately all contaminated clothing.
P363	Rinse skin with water [or shower].	
P304+P340	Wash contaminated clothing before	
P310 P321	IF INHALED: Remove person to fre breathing.	sh air and keep comfortable for
P305+P351+P338	Immediately call a POISON CENTE	-R/doctor/\u2026
1 303 1 33 1 1 330	Specific treatment (see on this la	
	IF IN EYES: Rinse cautiously with v	
	contact lenses, if present and easy	
P405	Store locked up	
P501	Dispose of contents/container to	

(c) Hazards not otherwise classified (HNOC)

Not applicable

(d) Unknown Toxicity

88.8 % of the mixture consists of ingredient(s) of unknown toxicity

11.5 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

88.8 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

58.7 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

58.7 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

58.7 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

(e) Other information

Very toxic to aquatic life with long lasting effects.

REPORT

Version: V1.4

NO.:CS201216148ASD

(f) Interactions with Other Chemicals

No information available.

Section 3- Composition/Information On Ingredients

Chemical Name	CAS Number	Weight (%)	Trade Secret
Iron	7439-89-6	39.2	*
Manganese dioxide	1313-13-9	6.2	*
Potassium hydroxide	1310-58-3	38.4	*
Zinc	7440-66-6	4.3	*
Carbo	7782-42-5	11.9	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4- First-aid Measures

Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Section 5- Fire-fighting measures

(a) Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

(b) Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

(c) Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

(d) Hazardous Combustion Products

Carbon oxides.

(e) Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6- Accidental Release Measures

(a) Personal precautions, protective equipment and emergency procedures

If the battery is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate. Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the battery happens, liquid could be absorbed with sand, earth or other inert substance and contaminated area should be ventilated meantime.

Version: V1.4
REPORT

NO.:CS201216148ASD

(b) Environment precautions

Do not allow product to reach sewage system or any water source.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(c) Methods and material for containment and cleaning up

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

Section 7- Handling and Storage

(a) Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

(b) Conditions for safe storage, including any incompatibilities Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases

Section 8- Exposure Controls/Personal Protection

(a) Control parameters

Chemical Name	ACGIH TLV	OSHA PEL		NIOSH IDLH	
Manganese dioxide 1313-13-9	TWA: 0.02 mg/m ³ Mn respirable particulate matter TWA: 0.1 mg/m ³ Mn inhalable particulate matter	(vacated) Ceiling: 5 r Ceiling: 5 mg/m ³		TW	: 500 mg/m ³ Mn A: 1 mg/m ³ Mn L: 3 mg/m ³ Mn
Potassium hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 r	(vacated) Ceiling: 2 mg/m ³		iling: 2 mg/m ³
Zinc 7440-66-6	STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction		Ceiling TWA: 5 m	H: 500 mg/m ³ g: 15 mg/m ³ dust ng/m ³ dust and fume : 10 mg/m ³ fume
Carbo 7782-42-5	TWA: 2 mg/m 3 respirable particulate matter all forms except Carbo fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural			H: 1250 mg/m ³ 5 mg/m ³ respirable dust
Chemical name	Alberta	British Columbia			Quebec

Version: V1.4
REPORT

٨	IO	::CS20	121	161	48A	SD

148ASI)					
	TWA: 0.2 mg/n	n ³	TWA: 0.2 mg/m ³	TWA: 0.02 mg/m ³ TWA: 0.1 mg/m	TWA: 0.2 mg/m ³	
	Ceiling: 2 mg/n	n ³	Ceiling: 2 mg/m ³	CEV: 2 mg/m ³	Ceiling: 2 mg/m ³	
	TWA: 2 mg/m	3	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	
1		ed by the	Court of Appeals decision	on in AFL-CIO v. OSHA	, 965 F.2d 962(11th	
e engii	neering contro	ols				
protect	ion measures	, such as	s personal protective ed	quipment		
	Face protection	on shield.				
ly	•	_		Long sleeved clothing.	Chemical resistant	
	No protective	equipme	nt is needed under norma	al use conditions. If exp	osure limits are	
y No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.						
smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash allowed.					/face protection. . Regular cleaning of re breaks and	
;	Section 9-	- Phys	sical and Chemi	cal Properties		
		Solid				
		No information available				
		No information available				
рН			No information available			
Melting point/freezing point			No information available			
Boiling Point and Boiling range			Not Available			
	ining range					
	illig range	Not Ava				
ammab s	ility or	Not Ava	ilable			
	Vacat Cir., 1	Ceiling: 2 mg/m TWA: 2 mg/m TWA: 2 mg/m Vacated limits revoke Cir., 1992). e engineering control Showers Eyewash static Ventilation system of the contection measures Face protection measures Face protection measures Wear protective exceeded or in Handle in accompose when in Avoid contact Contaminated equipment, we immediately a contaminated Section 9- reezing point	Ceiling: 2 mg/m³ Ceiling: 2 mg/m³ TWA: 2 mg/m³ Vacated limits revoked by the Cir., 1992) . e engineering controls Showers Eyewash stations Ventilation systems Protection measures, such as Face protection shield. Wear protective gloves apron. Impervious gloves apron. Section 9- Physical Solid Section 9- Physical Solid No information in No information points. No information point No information points.	TWA: 0.2 mg/m³ Ceiling: 2 mg/m³ Ceiling: 2 mg/m³ TWA: 2 mg/m³ TWA: 2 mg/m³ TWA: 2 mg/m³ TWA: 2 mg/m³ Vacated limits revoked by the Court of Appeals decision Cir., 1992). e engineering controls Showers Eyewash stations Ventilation systems protection measures, such as personal protective experienced, ventilation apron. Impervious gloves. No protective equipment is needed under normexceeded or irritation is experienced, ventilation Handle in accordance with good industrial hygic smoke when using this product. Take off contarton Avoid contact with skin, eyes or clothing. Wear Contaminated work clothing should not be allow equipment, work area and clothing is recommer immediately after handling the product. For envicontaminated protective equipment before re-use Section 9- Physical and Chemi Solid No information available No information available No information available No information available	Ceiling: 2 mg/m³ Ceiling: 2 mg/m³ CEV: 2 mg/m³ TWA: 2 mg/m³ TWA: 2 mg/m³ TWA: 2 mg/m³ Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA Cir., 1992) . e engineering controls Showers Eyewash stations Ventilation systems protection measures, such as personal protective equipment Face protection shield. y Wear protective gloves and protective clothing. Long sleeved clothing. apron. Impervious gloves. No protective equipment is needed under normal use conditions. If exp exceeded or irritation is experienced, ventilation and evacuation may be thandle in accordance with good industrial hygiene and safety practice. smoke when using this product. Take off contaminated clothing and wa Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye Contaminated work clothing should not be allowed out of the workplace equipment, work area and clothing is recommended. Wash hands before immediately after handling the product. For environmental protection, recontaminated protective equipment before re-use. Section 9- Physical and Chemical Properties Solid No information available No information available No information available No information available	

Version: V1.4
REPORT

NO.:CS201216148ASD

Not Available
Not Available
ion 10- Stability and reactivity
No information available.
Stable under normal conditions.
None under normal processing.
Hazardous polymerization does not occur.
Exposure to air or moisture over prolonged periods. Excessive heat.
Acids. Bases. Oxidizing agent.
Carbon oxides.
n 11 – Toxicological Information
Product does not present an acute toxicity hazard based on known or supplied information In case of rupture:
Specific test data for the substance or mixture is not available. Corrosive by inhalation.(based on components). Inhalation of corrosive fumes/gases may
cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. Harmful by inhalation.
hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs.

Version: V1.4
REPORT

NO.:CS201216148ASD

	Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.
--	-----------	---

Information on toxicological effects

S	ymptoms	Redness	Burning.	May	cause blindness.	Coughing	and/ or	wheezing.
---	---------	---------	----------	-----	------------------	----------	---------	-----------

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 749.00 mg/kg

ATEmix (inhalation-gas) 6,174.00 mg/L

ATEmix (inhalation-dust/mist) 2.06 mg/L

ATEmix (inhalation-vapor) 15.09 mg/L

Unknown acute toxicity

88.8 % of the mixture consists of ingredient(s) of unknown toxicity

11.5 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

88.8 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

58.7 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

58.7 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

58.7 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Iron	= 094 mg/kg (Pat)		
7439-89-6	= 984 mg/kg (Rat)	-	-
Manganese dioxide	= 0000 ma/kg / Dat)		
1313-13-9	= 9000 mg/kg (Rat)	-	-
Potassium hydroxide	= 204 ma/kg (Dot)		
1310-58-3	= 284 mg/kg (Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes burns.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.

Version: V1.4
REPORT

NO.:CS201216148ASD

Section 12- Ecological Information			
Aspiration hazard	No information available.		
STOT - repeated exposure	No information available.		
STOT - single exposure	No information available.		
Reproductive toxicity	No information available.		
NO03201210140A3D			

Ecological Toxicity		Very toxic to aquatic life with long lasting effects.			
Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)	
Iron		96h LC50: = 13.6 mg/L			
7439-89-6	-	(Morone saxatilis)	-	-	
Potassium hydroxide	-	96h LC50: = 80 mg/L (Gambusia affinis)	-	-	
1310-58-3		,			
Zinc 7440-66-6	96h EC50: 0.11 - 0.271 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.09 - 0.125 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 3.5 mg/L (Lepomis macrochirus) 96h LC50: = 7.8 mg/L (Cyprinus carpio) 96h LC50: = 0.24 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.59 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.41 mg/L (Oncorhynchus mykiss) 96h LC50: 0.211 - 0.269 mg/L (Pimephales promelas) 96h LC50: = 2.66 mg/L (Pimephales promelas) 96h LC50: = 30 mg/L (Cyprinus carpio) 96h LC50: = 0.45 mg/L (Cyprinus carpio) 96h LC50: 2.16 - 3.05 mg/L (Pimephales	-	48h EC50: 0.139 - 0.908 mg/L	
		mg/L (Pimephales promelas)			

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Log Pow
Manganese dioxide 1313-13-9	<0

Version: V1.4
REPORT

NO.:CS201216148ASD

Potassium hydroxide			
1310-58-3	0.83		
Section 13- Dispo	sal Considerations		
Waste treatment methods			
accordance with	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.		
Contaminated packaging Do not reuse emp	ty containers.		
California Hazardous Waste Codes 141			
This product contains one or more substances that are lis	sted with the State of California as a hazardous waste.		
Chemical name	California Hazardous Waste		
Potassium hydroxide 1310-58-3	Toxic Corrosive		
Zinc 7440-66-6	Ignitable powder Toxic		
Section 14 – Tran	nsport Information		
Proper Shipping Name Hazard Class NOT REGULATED NOT REGULATED N/A			
NOT REGULATED	D		
NOT REGULATED	NOT REGULATED		
CAO NOT REGULATE	NOT REGULATED		
ATA Proper Shipping Name Hazard Class NOT REGULATED NON REGULATED N/A			
MDG/IMO Hazard Class Marine Pollutant NOT REGULATED N/A Product is a marin	D ne pollutant according to the criteria set by IMDG/IMO		
RID NOT REGULATED	NOT REGULATED		
ADR NOT REGULATED	NOT REGULATED		
ADN NOT REGULATED	NOT REGULATED		
Section 15- Regu	latory information		

Version: V1.4
REPORT

NO.:CS201216148ASD

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS)

Not applicable

Persistent Organic Pollutants

Not applicable

Export Notification requirements

Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.

DSL/NDSL Contact supplier for inventory compliance status.

EINECS/ELINCS Contact supplier for inventory compliance status.

ENCS Contact supplier for inventory compliance status.

KECL Contact supplier for inventory compliance status.

PICCS Contact supplier for inventory compliance status.

Contact supplier for inventory compliance status.

Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS-No	<u>Percent</u>	SARA 313 - Threshold
			<u>Values %</u>
Manganese dioxide - 1313-13-9	1313-13-9	30.1	1.0
Zinc - 7440-66-6	7440-66-6	8.2	1.0

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

REPORT

Version: V1.4

NO.:CS201216148ASD

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name CWA - Reportable	Quantities	CWA - Toxic Pollutants CWA - Priority	Pollutants	CWA - Hazardous
Potassium hydroxide	1000 lb			Х
1310-58-3				
Zinc		X	X	
7440-66-6				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Potassium hydroxide	1000 lb		RQ 1000 lb final RQ
1310-58-3			RQ 454 kg final RQ
Zinc	1000 lb		RQ 454 kg final RQ
7440-66-6			RQ 1000 lb final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Manganese dioxide	X		X	×	x
1313-13-9	^		^	^	^
Potassium hydroxide	X	X	X	X	
1310-58-3					
Zinc	X	×	X	Х	
7440-66-6	^	^	^	^	
Carbo	Х	X	X		
7782-42-5	^	^	^		

Section 16- Other Information

Version: V1.4
REPORT

NO.:CS201216148ASD

NFPA	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical
				Properties -

HMIS Health hazards 0 Flammability 0 Physical hazards 0 Personal Protection X

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet