



DISTRIBUTED BY:
 Northeast Battery, LLC
 240 Washington Street
 Auburn, MA 01501
 T: (800) 441-8824
 F: (508) 832-2706
 sales@northeastbattery.com

ULTRAPOWER SMALL VRLA BATTERIES

UltraPower UP-series of valve regulated lead-acid batteries are designed with AGM (absorbent glass mat) technology for general purpose applications with five-year design life. Our batteries comply to the most popular international standards, such as IEC60896-21/22, BS6290-4, Eurobat Guide. The battery container and cover are available in flame retardant cases upon request. All batteries are DOT approved.

You can expect our batteries to meet all industry standards. We have obtained CE approval for all types of batteries. Our batteries are compatible with the requirements of world-level equipment.

Our applications engineering team works with our partners' engineering and technical design teams to ensure that the battery backup power solution we provide is a perfect match for the requirements of the customer's application.

Model Number	Voltage (VDC)	Capacity AH (C20)	Dimensions:			Weight (LBS)	Terminal Type	Case QTY	Pallet QTY
			L"	W"	H"				
UP1250F1	12	5	3.54	2.76	3.98	3.35	F1	10	950
UP1270F1	12	7	5.94	2.56	3.70	4.18	F1	10	640
UP1270F2	12	7	5.94	2.56	3.70	4.18	F2	10	640
UP1290F2	12	9	5.94	2.56	3.70	6.18	F2	5	540
UP12120F2	12	12	5.94	3.86	3.66	8.03	F2	6	432
UP12180NB	12	18	7.13	2.99	6.57	11.59	F3	4	284
UP12220-IT	12	22	7.13	2.99	6.57	12.76	F13	4	240
UP12350NB	12	35	7.75	5.11	6.25	21.01	F7	2	150
UP645F1	6	4.5	2.76	1.85	3.98	1.48	F1	20	2180
UP6120F1	6	12	5.95	1.97	3.70	3.99	F1	10	780



FOR A WORLD OF APPLICATIONS:

- ✚ Automated Teller Machines
- ✚ Computers
- ✚ Electric Toys & Hobby
- ✚ Fishing / Hunting Gear
- ✚ Geophysical Equipment
- ✚ Power Tools & Equipment
- ✚ Switchgear & Controls
- ✚ Uninterruptible Power Supplies
- ✚ Wheelchairs
- ✚ Cash Registers
- ✚ Electric Bikes & Scooters
- ✚ Emergency Lighting
- ✚ Fire & Security Systems
- ✚ Medical Devices
- ✚ Solar / Alternative Energy
- ✚ Telecommunications / CATV
- ✚ Utility (Auto-Reclosures)

TERMINAL CONFIGURATIONS:

